Dane aktualne na dzień: 29-03-2024 09:31

Link do produktu: https://www.marpolserwis.pl/minikoparka-kubota-k008-3-p-1338.html



Minikoparka Kubota K008-3

Opis produktu


Minikoparka Kubota K008-3 jest to najmniejsza minikoparka dostępna w ofercie tego producenta. Charakteryzuje się ona szeroką gamą prac jakie może wykonywać. Operator wykonując roboty budowlane jest dodatkowo zabezpieczony wytrzymałym metalowym stelażem, który ma możliwość regulacji oraz jest zaprojektowany dla jak najlepszego bezpieczeństwa operatora.

SPECIFICATIONS

*with rubber shoe type

Machine weight	Rubber crawler		kg	980
Bucket capacity, std. SAE/CECE			m^3	0.022/0.018
Bucket width	with side teeth		mm	368
	without side teeth		mm	350
Engine	Model			D722-BH-5
	Type			Water-cooled, diesel engine E-TVCS (Economical, ecological type)
	Output ISO90249		PS/rpm	10.2/2050
			kW/rpm	7.4/2050
	Number of cylinders			3
	Bore × stroke		mm	67 × 68
	Displacement		cc	719
Overall length			mm	2750
Overall height			mm	2230
Swivelling speed			rpm	8.3
Rubber shoe width			mm	180
Tumbler distance			mm	900
Dozer size (width × height)			mm	700/860 × 200
Hydraulic pumps	P1, P2			Gear pump
	Flow rate		ℓ/min	10.5 + 10.5
	Hydraulic pressure		MPa (kgf/cm^2)	16.7 (170)
Max. digging force	Arm		kN (kgf)	4.5 (460)
	Bucket		kN (kgf)	9.8 (1000)
Boom swing angle (left/right)			deg	55/60
Auxiliary circuit	Flow rate		ℓ/min	21.0
	Hydraulic pressure		MPa (kgf/cm^2)	170
Hydraulic reservoir			ℓ	12.5
Fuel tank capacity			ℓ	12.0
Max. travelling speed			km/h	2.0
Ground contact pressure			kPa (kgf/cm^2)	24.3 (0.25)
Ground clearance			mm	150

WORKING RANGE




Unit: mm

LIFTING CAPACITY

kN (ton)

Lift Point Height	Lifting point radius (1m)			Lifting point radius (2m)			Lifting point radius (2.5m)		
	Over-front		Over-side	Over-front		Over-side	Over-front		Over-side
	Blade Down	Blade Up		Blade Down	Blade Up		Blade Down	Blade Up	
2.0 m	-	-	-	1.9 (0.20)	1.5 (0.15)	1.2 (0.13)	-	-	-
1.0 m	-	-	-	2.0 (0.21)	1.5 (0.15)	1.2 (0.12)	1.7 (0.17)	1.0 (0.10)	0.8 (0.09)
0 m	6.0 (0.61)	3.8 (0.39)	2.9 (0.29)	2.2 (0.23)	1.3 (0.14)	1.1 (0.11)	1.5 (0.16)	1.0 (0.10)	0.8 (0.08)
-1.0 m	3.6 (0.37)	3.6 (0.37)	2.9 (0.30)	1.3 (0.13)	1.3 (0.13)	1.0 (0.11)	-	-	-

Please note:
* The lifting capacities are based on ISO 10567 and do not exceed 75% of the static tilt load of the machine or 87% of the hydraulic lifting capacity of the machine.
* The excavator bucket, hook, sling and other lifting accessories are not included on this table.



Dane techniczne:

Model silnika	KUBOTA-Diesel D222-BH-5
Pojemność	719 cm3
Moc silnika KM / obr-min	10,2 / 2050
Moc silnika kW / obr-min	7,4 / 2050
Głębokość kopania *	1720 mm / –
Wysokość unoszenia*	2870 mm / –
Szerokość	700 / 860 mm
Wysokość z kabiną	–
Wysokość z zadaszeniem	–
Siła kopiąca łyżki	9,8 kN
Siła kopiąca ramienia*	4,5 kN / –

Przepływ l/min	21 l/min
max ciśnienie Mpa (kgf/cm2)	16,7 (170)
Maksymalna prędkość jazdy	2.0 km/h
Prześwit	150 mm
Waga kabina / zadaszenie kg *	980 /-

Więcej informacji doradca techniczno-handlowy 604-318-523, 605-105-147